



Bars / Ice Cream Parlors / Coffee Shops



Gift Shops / Dollar Stores



Pizza / Table Service / Quick Service / Liquor Stores



Cafeterias / Delis

Best-in-Class Value Fanless POS Touch Screen Terminal



Vivid LED Backlight for Reliability and Energy Savings

The high performance SAM4S SPT-4740 touch screen terminal with a **dual-core fanless** CPU is designed to reliably and efficiently power demanding POS software applications in hospitality, quick service, grocery, and retail markets.

- 15" LCD with ELO® 5-Wire Resistive Touch
- Intel Celeron 1037U Dual Core 1.8GHz Fanless Processor
- **2GB RAM** Standard; Expandable to **4GB**
- Compatible with Popular Application Software
- Easily Wall Mountable
- Variety of Optional Integrated Customer Displays
- Connection Panel Allows Cables to Be Hidden and Routed Neatly Through the Base and Out the Rear of the Terminal



SPT-4740 Touch Screen Terminal



Optional Integrated 15" Rear LCD Customer Display



Optional Integrated 7" Rear LCD Customer Display



Optional Integrated VFD Customer Display



Tool-Free Access to Hard Disk Drive and RAM Optimizes Serviceability

Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 15", 9.7" or 7" LCD Customer Displays
- Encrypting Triple Track Card Reader
- Integrated Triple Track Card Reader with Integrated Fingerprint Reader
- Solid State Drive
- SATA Compact Flash Adaptor
- WiFi Module
- Wall Mount Bracket with Standard VESA Configuration

Applications

The attractive, powerful SPT-4700 fanless terminal is ideal for harsh environments like pizza, quick service restaurants, bakeries and industrial shop floors and for processor intensive applications including table service, retail scanning and many more:


- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video
- Table Service
- Training
- Unattended Workstations

Connectivity

- A** Drawer Voltage Selector Switch
- B** Cash Drawer
- C** Parallel
- D** Line-Out
- E** Mic-In
- F** Line-In
- G** USB (2)
- H** LAN
- I** COM1 (Powered)
- J** COM2 (Powered)
- K** USB (2)
- L** COM3 (Powered)
- M** VGA
- N** COM4 (Powered)
- O** DC Out (For Rear LCD)
- P** DC In (Power)

Specifications

| | | |
|--------------------------------|---|-----------|
| Processor: | Intel Celeron 1037U 1.8GHz Fanless | |
| Cores / Threads | Dual Core / 2 Threads | |
| Cache Memory: | 2MB | |
| Bus Speed: | 5 GT/s (Giga Transfers per Second) | |
| Display LCD: | Bezeled 15" LCD with LED Backlighting | |
| Resolution: | 1024 x 768 | |
| Brightness: | Adjustable Up to 350 cd/m2 | |
| Integrated Speakers: | Integrated 2 Watt Speakers | |
| Chipset (PCH): | NM70 | |
| Touch Panel: | 5-Wire Resistive Touch | |
| MCR: | Integrated USB Interface Triple Track MCR | |
| Hard Drive: | 2.5" With SATA Interface | |
| RAM Memory (2 Slots): | 2GB SODIMM DDR3 (1600MHz) Expandable To 4GB | |
| Video Memory: | Shared System Memory Up To 512MB | |
| Compact Flash: | Optional SATA Adaptor | |
| Serial Ports: | COM1, COM2, COM4 = DB9M With Pin 9 Voltage (0V/+5V/+12V) Selectable By BIOS / COM3 = RJ45 Pin 1 Voltage (0V+5V/+12V) Selectable By Jumper COM5 for Touchscreen / COM6 = RJ45 for Customer VFD | |
| Parallel Port: | One DB25F | |
| USB Ports: | 6 V2.0 (2 Left Side / 4 Bottom) | |
| Cash Drawer Port: | RJ11, 12V or 24V Selectable By Switch (Maximum 2 Drawers – Supports Open/Close) | |
| Keyboard / Mouse Port: | Not Applicable (Use USB Port) | |
| LAN Port: | RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111E | |
| VGA Port: | One DB15F Display Port For Second LCD (Maximum Resolution 2048 x 1536) | |
| Audio Port: | One Line-In / One Line-Out | |
| Mic Port: | One Mic-In | |
| Power Supply: | 60W, 12V/5A External Power Adaptor 100-240V 50-60Hz | |
| Current / Power Usage: | 0.25A / 27W (110V Idle Environment) | |
| Operating Temperature: | 32° F to 104° F (0° C to 40° C) | |
| Compatible O/S: | POSReady 2009 / POSReady 7 / Windows Pro Embedded 7 / Windows Pro 8 / Windows Embedded 8 Industry Pro | |
| Dimen. / Weight – Base: | 11"W x 7-3/8"H x 8-5/8"D | |
| Overall: | 14-1/8"W x 12-1/8"H x 8-5/8"D | 12.8 lbs. |
| Shipping Carton: | 20-1/4"W x 13"H x 16"D | 17.5 lbs. |
| Safety and EMI: | FCC, RoHS | |



Two USB Ports on the Left Side

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

© 2014, Printed in U.S.A.

Lit-254

SAM4S